

700HC14A24L

Allen-Bradley 700-HC Plug In Relay 7A 4CO 240VAC Gold Contacts Low Energy Rating 10V 1mA with PL



Allen-Bradley

by ROCKWELL AUTOMATION
GENERAL PURPOSE RELAYS



Component type	Switching relay
Range	Panel Mount and Power Relays
Model	N/A
Product status	Existing

ELECTRICAL

Nominal current	7.0 A
Nominal voltage AC	250.0 V
Max. rated operation voltage Ue AC	277.0 V
Number of contacts as change-over contact	4.0
Rated switching power at AC-1	1750.0 VA
Rated switching power at AC-15, 230V	350.0 VA
Breaking capacity at DC-1, 30V	7.0 A
Voltage type for actuating	AC
Control supply voltage Us at AC 50HZ	240.0 V
Control supply voltage Us at AC 60HZ	240.0 V
With LED indication	Yes
Type of electric connection	Plug-in connection
Electrical life at Un, In (service cycles)	100000.0 cycles
Operating voltage	19.2 - 26.4 V

CONSTRUCTION

Material contact	Other not-copper alloys
Suitable for plug-in socket mounting	Yes
Degree of protection (IP)	IP20
Material of contact surface	Gold

MECHANICAL

Mechanical life (service cycles)	2.0E7 cycles
----------------------------------	--------------

DIMENSIONS

Width	20.7 mm
Height	27.7 mm
Depth	37.2 mm

ENVIRONMENT

Operating temperature	-30 - 55 °C
-----------------------	-------------