

DINTMS632

NHP DIN-T Main Switch 2Pole 63A



Component type	Miniature circuit breaker (MCB)
Range	DIN-T MCB
Model	N/A
Product status	Existing

NHP DIN-T miniature circuit breakers are high-performance electrical protection devices offering a comprehensive range of features to meet the needs of any project. These MCBs are available in a variety of short circuit ratings ranging from 6kA, 10kA and 15kA, with current ratings from 0.5A through to 125A in variety of B, C or D trip curves. These MCBs are available in 1P, 2P, 3P and 4P housings.

ELECTRICAL

Rated current	63.0 A
Number of poles (total)	2.0
Rated voltage	415.0 V
Frequency	50 - 60 Hz
Voltage type	AC/DC
Rated impulse withstand voltage Uimp	8.0 kV
Concurrently switching neutral conductor	Yes

CONSTRUCTION

Degree of protection (IP)	IP40
---------------------------	------

MECHANICAL

Connectable conductor cross section solid-core	1 - 50 mm ²
--	------------------------

DIMENSIONS

Height	86.0 mm
Width	36.0 mm
Width in number of modular spacings	2.0
Depth	80.0 mm
Weight	0.24 kg

ENVIRONMENT

Pollution degree	3.0
Rated surrounding temperature without derating	30.0 °C
Ambient temperature during operating	-5 - 40 °C

DINTMS632

NHP DIN-T Main Switch 2Pole 63A



DIMENSIONAL DIAGRAM

